



CONTINUED ON OTHER SIDE

3 OPEN BATTERY DOOR AND INSERT 2X 18650*
*FOLLOW BATTERY ORIENTATION (+/-)

Carefully fill with e-liquid.
Please wait 5 minutes
before vaping.



Push in the direction of the
arrow, to slide open top cap



REFILLING THE TANK



2 SLIDE CAP OPEN AND TOP FILL


1 ATTACH TANK

INNOKIN PLEX + PROTON QUICK START GUIDE



FLIP FOR MORE INFO

4 POWER ON THE PROTON!




5 SELECT COIL OR MODE
(USE JOYSTICK TO
NAVIGATE AND SELECT).

6 CHECK COIL FOR RECOMMENDED WATTAGE /
TEMPERATURE RANGE.
START LOW AND INCREASE TO TASTE.



WATTAGE/SS316L/Ni200
CUSTOM T.C. MATERIALS
CUSTOM OUTPUT*
OUTPUTS BATTERY
VOLTAGE*
*WATTAGE ONLY



ADJUST ACCENT COLORS
AND OTHER FUNCTIONS.


JOYSTICK TO SELECT.
FIRE PANEL TO EXIT.

WATTAGE MODE



BATTERY LIFE
LOCK ICON
WATTAGE (6-235W)
TC: TEMPERATURE
SS316L/Ti/Ni200
150-315C/300-600F
PRE-HEAT WATTAGE
PUFF TIME / CUT-OFF
COIL RESISTANCE Ω
COIL TYPE (MODE)
VOLTAGE

TEMP CONTROL MODE



ENJOY THE VAPOR!

For full content, please refer to user manual on the product page at INNOKIN.COM

QUICK REFERENCE GUIDE



FIRING PANEL



JOYSTICK (DIRECTIONAL + CLICK)

CLICK 3X Power ON/OFF

CLICK 3X Access Menu: Coil Type/Modes, Settings
Click Joystick To Confirm Selection
Firing Panel To Exit To Main

HOLD Vape Lock / Unlock

HOLD View 2nd Screen Info:
- Coil Resistance
- Battery Voltage
- Puff Count

HOLD or Wattage: Increase WATTAGE MODE

HOLD or Wattage: Decrease

HOLD T.C.: Increase T.C. MODE

HOLD T.C.: Decrease

HOLD Pre-heat (T.C. Mode)

SETTINGS

Vape Cutoff: Select Vape Cutoff
Screen: Timeout, Dim Time, Brightness
C/F: Set Celsius - Fahrenheit
Color: Change Theme Color
Puff Count: Extended Puff Count
Firmware: Version / Reset / Update

SUPPORT

facebook.com/Innokin.Technology
 instagram.com/innokintechnology
 twitter.com/innokintech
 reddit.com/r/innokin
 support@innokin.com